AGO 5

AGO 5" Twin-Bore CI Borewell Cap

Twin-bore 5" cap plate clamping two column pipes, or one column pipe with a separate cable or sounding tube.



Sizes	Minimum order	Lead time	Price
5", 6", 7"	**50 pieces**	**10 - 14 days**	**Quoted per order**

What this part is

A twin-bore borewell cap carries two separate clamped openings in a single plate. It is used where a bore runs two column pipes from two pumps, or where a single pump installation needs a dedicated second opening for a water-level sounding pipe, dosing line or armoured cable run that must not be pinched inside the main clamp.

Specification

Pattern	AGO twin
Nominal size	5 inch
Openings	2, on a common split line
Material	Grey cast iron FG 200
Clamp type	Integral split, two-bolt
Bore centres	To customer drawing
Finish	Shot blasted, enamel painted

Material

- Grey Cast Iron FG 200 / FG 260 (IS 210)

Typical applications

- Twin-pump borewells
- Bores with water-level sounding tubes
- Installations with separate armoured cable entry

How we make it

Same plate thickness and clamp construction as our single-bore AGO 5", with two machined clamp bores set side by side on a common split line. One pair of bolts closes both halves together, which keeps installation time the same as a

single-bore cap.

Bore centres and the two bore diameters can be cast to your drawing - the standard pattern takes two equal column pipes, and a reducing version takes one column pipe with a smaller sounding tube.

Questions

Can the two bores be different sizes?

Yes. A reducing twin cap with one column-pipe bore and one smaller sounding-tube bore is a standard variant. Give us both pipe outside diameters and the centre distance you need.

Is the clamp strong enough to hold the pump assembly?

Yes. The split clamp is cast as part of the plate, not welded on, and is tightened with two high-tensile bolts. It is rated to carry the hanging weight of the column pipe, cable and submersible pump for the size it is supplied against.

What finish is supplied as standard?

Standard supply is shot-blasted and enamel painted in our green finish. Primer-only, black bitumen and hot-dip galvanised finishes are available against bulk orders.

To order

Send us four measurements and we can quote first time: bore casing outside diameter, column pipe outside diameter, approximate column run in metres, and cable type. Clamp bores are machined to your column pipe.